

# Speedograph Richfield

Speedograph Richfield Ltd.  
Rolleston Drive, Arnold, Nottingham, NG5 7JR  
Telephone: 0044 (0)115 926 4235  
Facsimile: 0044 (0)115 920 9912  
email: info@speedographrichfield.com

## SPEEDOMETER RECALIBRATION

To have a speedometer recalibrated, the following exercise is all that is required for you to supply the information we need. **PLEASE FOLLOW THESE INSTRUCTIONS EXACTLY.**

- 1 Disconnect Flexible drive from instrument end.
- 2 Mark drive wheel tyre with chalk line, masking tape, or similar.
- 3 Mark body or chassis with a line corresponding to the line on the tyre.
- 4 Ensure tyres are inflated to correct pressure.
- 5 Push vehicle along the ground in a straight line for 6 turns of the drive wheel whilst an assistant counts the number of turns the inner speedometer cable makes, to the nearest 1/8 of a turn. (To facilitate ease of counting a cardboard arrow can be made and pressed onto the end of the inner cable.)
- 6 Supply make and size of tyre.

We need to know: a) Number of turns of inner cable for 6 turns of drive wheel

b) Make and size of tyre.

c) Make / part number of speedometer.

Please complete:


Do you want the mileage left at .....

YES/ NO

Or set back to zero?

YES/ NO